

# PRO line

Money changing machines for any requirements



Long manufacturing tradition combined with the latest technology

## Dual Coin PRO



## The ideal solution for dispensing large amounts of two different coin/token denominations

Its exceptional structural strength, reinforced closing mechanisms and ccTalk protocol make it one of the most secure change machines on the market. The 32-bit CPU provides notable functions, such as importing/exporting configuration parameters, exporting accounting data and the useful function of machine cloning.



#### Features

- Distribution of coins and tokens (bonus function for tokens)
- Coins/tokens dispensed automatically or manually
- New 32-bit CPU with SD-Card: Exporting of accounting data and importing of configuration parameters via SD-Card
- Machine cloning function
- Separate dispensing of coins and tokens contained in different hoppers, can be selected using the appropriate button

- Internal on/off controls to prevent tampering
- Pivoting door to facilitate dispenser-loading and cash box removal operations
- Additional doors to recharge the change machine (on the cover)
- Installation: wall mounted by means of 3 anchoring bolts to be inserted at the back of the device; countertop; free standing

Dual Coin PRO can be equipped with the NV9 USB banknote reader with built-in stacker to stack up to 600 banknotes

#### Installed peripherals

- 2 Evolution hoppers with extensions
- NV9 USB/NV10 USB Banknote reader

#### Optional peripherals

• RM5 HD coin validator

#### Tools

#### MultiConfig

Software to configure the change machine

#### Optional accessories

- BRAIN remote control device
- Support base
- · Reprogrammable lock
- Coin/token collection cups (max h 120 mm
  Ø 145 mm)
- · Cup dispensing tube
- · Steel protective bars

## Technical specifications Change machine Change machine with support base

Dimensions (LxHxW)	400 x 805 x 409 mm	400 x 1,620 x 409 mm
Weight	43 kg	60 kg
Power supply	230 Vac - 50 Hz	230 Vac - 50 Hz
Power consumption	60 W max	60 W max
Operating temperature	3°C ÷ 50 °C	3°C ÷ 50 °C

Coin Capacity	0,5 €	1€	2€
2 Evolution hoppers with extensions	7,000	7,000	6,500
Cash box			4,600

## Easy PRO



### The versatile best selling machine

The 32-bit CPU provides functions which are present only in the change machines of higher range and price, such as importing/exporting configuration parameters, exporting accounting data and the useful function of machine cloning. The reinforced closing mechanisms make Easy PRO one of the most secure change machines in the market with regards to attempts of tampering and fraud.



#### Features

- Connection of peripherals via ccTalk
- Distribution of coins or tokens (Bonus function for tokens)
- Coins/tokens dispensed automatically or manually
- New 32-bit CPU with SD-Card export Exporting of accounting data and importing of configuration parameters via SD-Card
- Machine cloning function
- Special cover for the dispenser's extension: prevents coins from falling out if the machine is tipped over

- Internal on/off controls to prevent tampering
- Pivoting door to facilitate dispenser-loading and cash box removal operations
- Holes in the cabinet for fastening it to other machines or to external structures (columns or pillars)
- Wide range of installation options: wall mounted (with the Easy UP kit); countertop; wall mounted by means of 3 anchoring bolts to be inserted at the back of the device; free standing on support base (optional)

easy PRO fits perfectly into all environments: shopping centres, gyms, airports, service stations, arcades, offices, bars and internet cafés

#### Installed peripherals

- Evolution hopper with extension
- NV9 USB/NV10 USB Banknote reader

#### Optional peripherals

• RM5 HD coin validator

#### Tools

#### MultiConfig

Software to configure the change machine

#### Optional accessories

- BRAIN remote control device
- Kit for reinforcing change machines already in use
- Support base
- Easy UP installation kit
- · Reprogrammable locks
- · Steel protective bars

## Technical specifications Change machine Change machine with support base

Dimensions (LxHxD)	257 x 473 x 353 mm	257 x 1,436 x 353 mm
Weight	25 kg	38 kg
Power supply	230 Vac - 50 Hz	230 Vac - 50 Hz
Power consumption	60 W max	60 W max
Operating temperature	3 °C ÷ 50 °C	3 °C ÷ 50 °C

Coin Capacity	0.5€	1€	2€
Hopper Evolution	2,400	2,400	2,200
Cash box		1,600	

## Twin Jolly PRO



### Robust and reliable with excellent security performance

Twin Jolly PRO offers the same security, design and functionality of the Jolly PRO, in a more performing unit. The ccTalk protocol offers high levels of protection from tampering and electronic frauds, while the new 32-bit CPU allows access to innovative functions for managing accounting data and configuration, and useful machine cloning function.



#### Features

- Connection of peripherals via ccTalk
- Distribution of two different types of coins and tokens. (Bonus function for various types of tokens)
- Coins/tokens dispensed automatically or manually
- New 32-bit CPU with SD-Card export (Exporting of accounting data and importing of configuration parameters via SD-Card)
- Machine cloning function
- Technical compartment separated from the cash compartment: the payment systems are secure

- The hoppers can be recharged externally, without accessing the cash compartment, for higher security
- The collection of large amounts of coins and tokens is facilitated by the pre-set compartment for free dispensing for cups collection
- A ballast can be placed at the base in a separate lockable compartment to ensure better stability and a higher security from theft

- Dispensing capacity equal to 6,800 1€ coins
- Cash box and hopper compartment protected by an 8-point locking mechanism

## Installed peripherals

- 2 Evolution hoppers with extensions
- NV10 USB Banknote reader

#### Optional peripherals

• RM5 HD coin validator

### Tools

#### MultiConfig

Software to configure the change machine

### Optional accessories

- BRAIN remote control device
- Coin/token collection cups (max height: 120 mm - diameter: 145 mm)
- Reprogrammable locks
- Steel protective bars

## Technical specifications

Dimensions (LxHxW)	340 x 1,450 x 475 mm
Weight	72 kg
Power supply	230 Vac – 50 Hz
Power consumption	60 VA (max)
Operating temperature	3 °C ÷ 50 °C

Coin Capacity	0.5€	1€	2€
2 Evolution hoppers with extension	6,800	6,800	6,400
Cash box		10,000	

## Jolly PRO



#### Slim and versatile

Designed to fit into different environments, Jolly PRO is a complete and versatile change machine thanks to its wide display, removable SD-Card and 32-bit CPU. Despite its reduced size, Jolly PRO offers excellent dispensing capacity (3,400 1 € coins), being the ideal solution when space is an issue.



#### **Features**

- Connection of peripherals via ccTalk
- Distribution of coins or tokens (Bonus function for tokens)
- Coins/tokens dispensed automatically or manually
- New 32-bit CPU with SD-Card export (Exporting of accounting data and importing of configuration parameters via SD-Card)
- Machine cloning function

- The collection of large amounts of coins and tokens is facilitated by the pre-set compartment for free dispensing for cups collection
- The structure protects the change machine against liquid spills
- A ballast can be placed at the base in a separate lockable compartment to ensure better stability and a higher security from theft
- Technical compartment, containing all the electronics and payment systems, isolated from the cash box compartment
- The hopper can be recharged externally, without accessing the cash compartment, for higher security

#### Installed peripherals

- 1 Evolution hopper with extension
- NV9 USB/NV10 USB Banknote reader

## Optional peripherals

RM5 HD coin validator

#### Tools

#### MultiConfig

Software to configure the change machine

#### Optional accessories

- BRAIN remote control device
- Coin/token collection cups (max height: 120 mm - diameter: 145 mm)
- Reprogrammable locks
- · Steel protective bars

#### Technical specifications

Dimensions (LxHxW)	200 x 1,450 x 475 mm
Weight	55 kg
Power supply	230 Vac – 50 Hz
Power consumption	60 VA (max)
Operating temperature	5 °C ÷ 50 °C

Coin Capacity	0.5 €	1€	2€
1 Evolution hopper with extension	3,400	3,400	3,200
Cash box		2,800	